Aufbauanleitung "IsoFrame Wave" Lagerraum Kit

Mounting instructions

Storage room with door
– 1600 x 1600 mm (63 x 63 inches)

Item.no: Midi IS-9420-1
Maxi IS-9420-2

Complete with:

	Midi IS-9420-1	Maxi IS-9420-2
1 Base post, 750 mm, adj. foot	IS-0750-EBM	IS-0750-EBM
1 Extension post, 750 m	IS-0750-EEM	IS-0750-EEM
1 Top post, 755 mm	IS-0755-ETM	IS-0755-ETM
2 Base post, 750 mm	IS-0750-BP	IS-0750-BP
2 Extension post, 750 mm	IS-0750-EP	IS-0750-EP
2 Top post, 755 mm	IS-0755-TP	IS-0755-TP
2 90° corner post, Base, wave cut	IS-W750-IB90	IS-W750-IB90
2 90° corner post, Center, 750 mm	IS-0750-IE90	--------
2 90° corner post, Top, 755 mm	IS-0755-IT90	--------
2 90° corner post, Center, 850 mm	--------	IS-0850-IE90
2 90° corner post, Top,855 mm	--------	IS-0855-IT90
2 Extension post, 200 mm, standard	--------	IS-0200-EP
1 Extension post, 200 mm, ext. Corner	--------	IS-0200-EEM
6 Straight beam, 800	IS-800-BS	IS-800-BS
6 Corner trims, 750/850	IS-0750-CT	IS-0850-CT
3 Corner trims, 770	IS-0770-CT	IS-0770-CT
4 Kickers & Hangers	IS-800-KHN	IS-800-KHN
1 Door, straight	IS-9458	IS-9458



Accessories

Coat hook
with straight beam 800mm
Item IS-9430



1 This unit is a 'Starter module'. Begin the first by first adding/connecting another module to your display.

2 The door unit can be installed at any of the four positions in the module.

3 As with all fixed-beam modules, be sure to level the complete storage room module before adding your graphic panels.

4 When you are ready, you will have 2 set of corner trim left, this will be mounted in each end of the wall.

www.pdflib.com